



## PRODUCT USE CHART

PRODUCT	USE	MAKEUP QUANTITY	
		Standard Units	SI-Metric Units
AQF-2™	Premium Grade Foamer	0.5 gal - 2 gal/100 gal	5.0 – 20.0 L/m <sup>3</sup>
AQUAGEL GOLD SEAL®	Viscosity	10 - 50 lbs/100 gal	12 – 60 kg/m <sup>3</sup>
AQUAGEL®	Viscosity	10 - 50 lbs/100 gal	12 – 60 kg/m <sup>3</sup>
BARAFOS®	Thinner	0.25 – 0.5 lb/100 gal	0.3 – 0.6 kg/m <sup>3</sup>
	Well Development	10 - 20 lbs/100 gal	12 – 24 kg/m <sup>3</sup>
BIO-BORE™	Horizontal Drlg. Fluid System	20 - 35 lbs/100 gal	24 – 42 kg/m <sup>3</sup>
BORE-GEL®	Horizontal Boring Fluid	25 - 50 lbs/100 gal	30 – 60 kg/m <sup>3</sup>
CON DET®	Wetting Agent	0.5 – 1.0 qt/100 gal	1.25 – 2.5 L/m <sup>3</sup>
DEXTRID®	Filtration Control	0.5 - 10 lbs/100 gal	0.6 – 12 kg/m <sup>3</sup>
DINOMUL®	Wellbore Stabilizing Fluid	1.0 – 2.0 gal/100 gal	10 – 20 L/m <sup>3</sup>
EZ-MUD® DP	Clay/Shale Stabilizer/Viscosifier	0.3 – 2.0 lbs/100 gal	0.4 – 2.4 kg/m <sup>3</sup>
EZ-MUD® GOLD	Clay/Shale Stabilizer/Filtration	0.5– 2.5 lbs/100 gal	0.6 – 3.0 kg/m <sup>3</sup>
EZ-MUD® PLUS	Clay/Shale Stabilizer/Viscosifier	0.5 – 2.0 qts/100 gal	1.25 – 5.0 L/m <sup>3</sup>
EZ-MUD®	Clay/Shale Stabilizer/Viscosifier	0.5 – 2.0 qts/100 gal	1.25 – 5.0 L/m <sup>3</sup>
LIQUI-TROL™	Filtration Control/Viscosifier	1.0 – 4.0 qts/100 gal	2.5 – 10 L/m <sup>3</sup>
NO-SAG®	Gel Strength Enhancer	0.25 – 2.5 lbs/100 gal	0.3 – 3.0 kg/m <sup>3</sup>
PAC™-L	Filtration Control	0.5 - 7 lbs/100 gal	0.6 – 8.4 kg/m <sup>3</sup>
PAC™-R	Filtration Control/Viscosifier	0.5 - 5 lbs/100 gal	0.6 – 6.0 kg/m <sup>3</sup>
PENETROL®	Penetration Rate Enhancer	0.5- 4 qts/100 gal	1.25 – 10.0 L/m <sup>3</sup>
POLY-BORE™	Borehole Stabilizer/Viscosifier	0.5 - 1 lb/100 gal	0.6 – 1.2 kg/m <sup>3</sup>
QUIK-FOAM®	Premium Grade Foamer	0.25 gal - 2 gal/100 gal	2.5 – 20.0 L/m <sup>3</sup>
QUIK-GEL®	Viscosity	15 - 35 lbs/100 gal	18.0 – 42.0 kg/m <sup>3</sup>
QUIK-TROL®	Filtration Control/Viscosifier	0.5 - 5 lbs/100 gal	0.6 – 6.0 kg/m <sup>3</sup>
QUIK-TROL® LV	Filtration Control	0.5 - 7 lbs/100 gal	0.6 – 8.4 kg/m <sup>3</sup>
Soda Ash	Calcium Remover/pH	1 – 2 lbs/100 gal	1.2 – 2.4 kg/m <sup>3</sup>
ZEOGEL®	Saltwater Viscosifier	35 – 75 lbs/100 gal	42.0 – 60.0 kg/m <sup>3</sup>